

Hiroyuki Miyoshi
Kyoto Sangyo University

Weak values as contextual values, categorically

Aharonov et al. introduced in quantum mechanics the notion of weak values which depend on post-selected states [AZV88]. Hosoya and Koga regarded weak values as *contextual values*, which clarified that they depend on the choice of post-selected states but the expectation value and the variance of them do not [HK11]. In this talk, we formulate contextual values in the form of categorical quantum mechanics of [AC04]. As an application, we discuss Ozawa's work on uncertainty relations [Oz03] in our abstract framework.

REFERENCES

- [AZV88] Yakir Aharonov, David Z. Albert, and Lev Vaidman, *How the result of a measurement of a component of the spin of a spin-1/2 particle can turn out to be 100*, Phys. Rev. Lett. vol.60 (1988), pp.1351–1354.
- [HK11] Akio Hosoya, and Minoru Koga, *Weak values as context-dependent values of observables and Born's rule*, J. Phys. A: Math. Theor. vol.44 (2011), 415303, 8pp. .
- [AC04] Samson Abramsky, and Bob Coecke, *A categorical semantics of quantum protocols*. In: Proc. of 19th IEEE conf. on Logic in Computer Science. pp.415–425 (2004).
- [Oz03] Masanao Ozawa, *Universally valid reformulation of the Heisenberg uncertainty principle on noise and disturbance in measurement*, Phys. Rev. A vol.67 (2003), 042105, 6 pp.,